

Package: QuantileNPCI (via r-universe)

September 16, 2024

Type Package

Title Nonparametric Confidence Intervals for Quantiles

Version 0.9.0

Maintainer Li Yan <li.yan@roswellpark.org>

Description Based on Alan D. Hutson (1999)

<[doi:10.1080/02664769922458](https://doi.org/10.1080/02664769922458)>, ``Calculating nonparametric confidence intervals for quantiles using fractional order statistics'', Journal of Applied Statistics, 26:3, 343-353.

License GPL-3

Encoding UTF-8

LazyData true

Suggests dplyr, kableExtra, knitr, rmarkdown, testthat (>= 2.1.0)

Depends R (>= 2.10)

RoxygenNote 6.1.1

VignetteBuilder knitr

NeedsCompilation no

Author Nicholas Hutson [aut], Alan Hutson [aut], Li Yan [aut, cre]

Date/Publication 2019-09-05 15:20:02 UTC

Repository <https://yan16.r-universe.dev>

RemoteUrl <https://github.com/cran/QuantileNPCI>

RemoteRef HEAD

RemoteSha 6fa1567037f5d9fc7ae8586cbd531d45d37035e3

Contents

exactBeta	2
flood	2
quantCI	3

Index

4

<code>exactBeta</code>	<i>Calculate lower and upper CI of a given quantile using exact method, based on beta distribution</i>
------------------------	--

Description

Calculate lower and upper CI of a given quantile using exact method, based on beta distribution

Usage

```
exactBeta(n, q, alpha)
```

Arguments

<code>n</code>	sample size
<code>q</code>	quantile
<code>alpha</code>	desired significance level

Value

a list of the lower and upper confidence limit of the quantiles. Values are between [0,1]

<code>u1</code>	lower confidence limit of the quantile
<code>u2</code>	upper confidence limit of the quantile

Examples

```
QuantileNPCI:::exactBeta(25, 0.5, 0.05)
```

<code>flood</code>	<i>The flood rate of Feature River and Blackstone River.</i>
--------------------	--

Description

A dataset containing the flood rate data, as presented in Hutson 1999 paper. Original source: Pericchi and Rodriguez-Iturbe (1995)

Usage

```
flood
```

Format

A data frame with 96 rows and 3 variables:

- loc** River name
- year** year of the record
- discharge** flood discharge rate

quantCI

quantCI

Description

Calculate nonparametric confidence intervals for quantiles using fractional order statistics,

Usage

```
quantCI(x, q, alpha, method)
```

Arguments

- | | |
|--------|--|
| x | vector of data |
| q | the quantile |
| alpha | the significance level |
| method | the method used for calculate the confidence interval. Options are "exact" or "approximate". |

Value

returns a list of 5 values:

- | | |
|----------|--|
| u1 | the lower confidence limit of the quantile |
| u2 | the upper confidence limit of the quantile |
| lower.ci | the estimated x value at u1 |
| qx | the estimate x value of at the quantile q |
| upper.ci | the estimated x value at u2 |

Author(s)

Nicholas Hutson

Examples

```
x <- c(3.5,2.4,2.1,1.3,1.2,2.2,2.6,4.2)
quantCI(x, q=0.5, alpha=0.05, method = "exact")
```

Index

* **datasets**

flood, [2](#)

exactBeta, [2](#)

flood, [2](#)

quantCI, [3](#)